

### 3.8: Mechanical and Electrical Vibrations

Trig background:

$$\cos(y \mp x) = \cos(x \mp y) = \cos(x)\cos(y) \pm \sin(x)\sin(y)$$

Let  $A = R\cos(\delta)$ ,  $B = R\sin(\delta)$  in

$$\begin{aligned} & A\cos(\omega_0 t) + B\sin(\omega_0 t) \\ &= R\cos(\delta)\cos(\omega_0 t) + R\sin(\delta)\sin(\omega_0 t) \\ &= R\cos(\omega_0 t - \delta) \end{aligned}$$

Amplitude =  $R$

frequency =  $\omega_0$  (measured in radians per unit time).

period =  $\frac{2\pi}{\omega_0}$

phase (displacement) =  $\delta$

Mechanical Vibrations:

$$mu''(t) + \gamma u'(t) + ku(t) = F_{external}, \quad m, \gamma, k \geq 0$$
$$mg - kL = 0$$

$m$  = mass,

$k$  = spring force proportionality constant,

$\gamma$  = damping force proportionality constant

Electrical Vibrations:

$$L \frac{dI(t)}{dt} + RI(t) + \frac{1}{C}Q(t) = E(t), \quad L, R, C \geq 0 \text{ and } I = \frac{dQ}{dt}$$

$L$  = inductance (henrys),

$R$  = resistance (ohms)

$C$  = capacitance (farads)

$Q(t)$  = charge at time  $t$  (coulombs)

$I(t)$  = current at time  $t$  (amperes)

$E(t)$  = impressed voltage (volts).

$$1 \text{ volt} = 1 \text{ ohm} \cdot 1 \text{ ampere} = 1 \text{ coulomb} / 1 \text{ farad} =$$
$$1 \text{ henry} \cdot 1 \text{ amperes} / 1 \text{ second}$$

$$mu''(t) + \gamma u'(t) + ku(t) = F_{external}, \quad m, \gamma, k \geq 0$$

$$r_1, r_2 = \frac{-\gamma \pm \sqrt{\gamma^2 - 4km}}{2m}$$

$$\gamma^2 - 4km > 0: u(t) = Ae^{r_1 t} + Be^{r_2 t}$$

$$\gamma^2 - 4km = 0: u(t) = (A + Bt)e^{r_1 t}$$

$$\gamma^2 - 4km < 0: u(t) = e^{-\frac{\gamma t}{2m}} (A \cos \mu t + B \sin \mu t)$$

$\mu =$  quasi frequency,  $\frac{2\pi}{\mu} =$  quasi period

Note if  $\gamma = 0$ , then

Critical damping:  $\gamma = 2\sqrt{km}$

Overdamped:  $\gamma > 2\sqrt{km}$

Suppose a mass weighs 64 lbs stretches a spring 4 ft. If there is no damping and the spring is stretched an additional foot and set in motion with an upward velocity of  $\sqrt{8}$  ft/sec, find the equation of motion of the mass.

$$\text{Weight} = mg: m = \frac{\text{weight}}{g} = \frac{64}{32} = 2$$

$$mg - kL = 0 \text{ implies } k = \frac{mg}{L} = \frac{64}{4} = 16$$

$$mu''(t) + \gamma u'(t) + ku(t) = F_{\text{external}}$$

$$[\gamma^2 - 4km < 0: u(t) = e^{-\frac{\gamma t}{2m}} (A \cos \mu t + B \sin \mu t)$$

Hence  $u(t) = (A \cos \mu t + B \sin \mu t)$  since  $\gamma = 0$ ].

$$2u''(t) + 16u(t) = 0$$

$$u''(t) + 8u(t) = 0$$

$$u(0) = 1, u'(0) = -\sqrt{8}$$

$$r^2 + 8 = 0 \rightarrow r^2 = -8 \rightarrow r = \sqrt{-8} = i\sqrt{8} = 0 + i\sqrt{8}$$

$$u(t) = e^{-\frac{\gamma t}{2m}} (A \cos \mu t + B \sin \mu t)$$

$$u(t) = A \cos \sqrt{8}t + B \sin \sqrt{8}t$$

$$u(0) = 1: 1 = A \cos(0) + B \sin(0) = A$$

$$u'(t) = -\sqrt{8}A \sin \sqrt{8}t + \sqrt{8}B \cos \sqrt{8}t$$

$$u'(0) = -\sqrt{8}: -\sqrt{8} = -\sqrt{8}A \sin(0) + \sqrt{8}B \cos(0)$$

$$B = -1$$

$$u(t) = \cos \sqrt{8}t - \sin \sqrt{8}t$$